



# **HGUIDE i200** **MEMS INERTIAL** **MEASUREMENT UNIT**

**Honeywell**

# HGUIDE i200 MEMS INERTIAL MEASUREMENT UNIT



Proven - Dependable - Accurate

## KEY HONEYWELL ADVANTAGES

- World-class inertial sensor development, calibration and compensation.
- Units feature a range of user configurable options with selectable output data rates and filtering.
- Multiple, configurable communication protocols.
- Proven reliability, dependability and ruggedness, through unit life.

The HGuide i200 is a high-performance micro-electro-mechanical system (MEMS) based inertial measurement unit (IMU) designed to meet the needs of applications across various markets including agriculture, AUVs, industrial equipment, robotics, survey/mapping, stabilized platforms, transportation, UAVs and UGVs. With industry standard communication interfaces and a wide-input voltage range the HGuide i200 is easily integrated into a variety of architectures. The extremely small size, light weight, and low power make the HGuide i200 ideal for many applications.

The HGuide i200 includes MEMS gyroscopes and accelerometers. In addition, the HGuide i200 employs an internal environmental isolation system to attenuate unwanted inputs commonly encountered in real world applications. The internal isolation and other proprietary design features ensure the HGuide i200 is rugged enough to meet the needs of the most demanding users.

The HGuide i200 is both hardware and software compatible with the HG4930 IMU.

The HGuide i200 is not ITAR controlled. Its Export Control Classification Number (ECCN) is 7A994.

## HGUIDE i200 IMU TYPICAL KEY CHARACTERISTICS

Volume/ Size	17 cm <sup>3</sup> (1 in <sup>3</sup> ) / 42 x 28 x 14 mm
Weight	35 grams
Power Consumption	0.5 Watts
Operating Temperature Range	-40°C to +85°C
Data Rate	300 Hz nominal (User configurable)
Gyro Operating Range	+/- 490 deg/s in all axes
Accelerometer Operating Range	±16g in all axes
Supply Voltages	+5.0 to +36 VDC
Bandwidth	200Hz at 90° phase, 400Hz at -3dB (Output frequency dependent)
Vibration	Random : 20-2000Hz MIL-STD-810G 2.2 grams Sinusoidal : 10-2000Hz 2g Peak Non-operating : 7.7G RMS
Shock	40g, 11ms per MIL-STD-810G 25g bump half-sine per IEC 60068-2-27
Communication Protocols	RS-422, 5V TTL, CAN
Asynchronous Baud Rate	Configurable: 921.6 Kbs default
Discrete Signals	Data ready output

## HGUIDE i200 IMU TYPICAL PERFORMANCE – ROOM TEMPERATURE

Marketing Part Number <sup>1</sup>	Gyro Bias Repeatability (°/hr 1σ)	Gyro Bias In-run Stability (°/hr 1σ)	ARW (°/√hr)	Accel Bias Repeatability (mg 1σ)	Accel Bias In-run Stability (mg 1σ)	VRW (m/s/√hr)
i200CA50	260	10	0.3	5	0.03	0.04

<sup>1</sup> When ordering direct from Honeywell, use part number 68910200-CA50.

## For More Information

[aerospace.honeywell.com/HGuide](http://aerospace.honeywell.com/HGuide)

## Honeywell Aerospace

2600 Ridgeway Parkway  
Minneapolis MN 55413  
[aerospace.honeywell.com](http://aerospace.honeywell.com)

N61-2534-000-000 | 08/20  
© 2020 Honeywell International Inc.

THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

**Honeywell**